

TONGFA

泰州市同发汽车配件有限公司

Taizhou Tongfa Automobile Fitting Co.,Ltd



>> 2022.03.20
JIANGSU TAIZHOU



TONGFA

泰州市同发汽车配件有限公司

Taizhou Tongfa Automobile Fitting Co.,Ltd

地址：泰州市海陵区鲍徐路2号

Address: No. 2, Baoxu Road, Hailing District, Taizhou City

电话：0523-86848149

Tel: 0523-86848149

手机：18052677777

Phone: 18052677777

网址：www.tz-tongfa.com

Website: www.tz-tongfa.com





公司简介

Company Profile

泰州市同发汽车配件有限公司，座落于泰州市经济开发区，位于328国道路口鲍徐路2号，水陆交通便捷，投资环境优雅。

企业现有员工260余名，工程技术人员达25名，占地面积4.3万平方米，拥有国内较为先进的630T铝型材挤压生产线。具备从原材料模具设计与制造、型材挤压、窗框成型、焊接抛光、总装测试出厂，形成一条完整的生产流水线。企业现有主导产品为铝合金汽车侧窗和工业铝材，年产量侧窗达十五万台套、铝材三千吨。

在知识经济时代，我们时刻注重产品自身的运行速度、产品更新换代速度，不断推陈出新，摒弃落后；崇尚以人为本、科技至上，时刻坚持把好的技术和产品回报给我们的用户。

Taizhou Tongfa Automobile Fitting Co.,Ltd is located in Taizhou Economic Development Zone, located at No. 2 Baoxu Road, the intersection of 328 National Road, with convenient land and water transportation and elegant investment environment.

The company has more than 260 employees, 25 engineering and technical personnel, covers an area of 43,000 square meters, has a relatively advanced 630T aluminum extrusion production line. Has from the raw material mold design and manufacturing, profile extrusion, window frame molding, welding and polishing, final assembly test factory, forming a complete production line.

The main products of the company are aluminum alloy automobile side Windows and industrial aluminum materials. The annual output of side Windows reaches 150,000 sets and aluminum materials 3,000 tons In the era of knowledge economy, we always pay attention to the running speed of the product itself, the speed of product renewal, constantly bring forth the new,



目录

Comtents

房车门系列/RV Door Series		
SLD单点锁房车门	SLD Single point lock RV Door	01
ELD刷卡锁房车门	ELD credit card lock RV Door	02
DLD房车门	DLD RV Door	03
TLD三联房车门	TLD Three point linkage lock RV Door	04
水滴门	Teardrop RV Door	05
拖挂式房车门	Trailer Door	06
单点刷卡锁门	Single point credit card lock RV Door	07
单点密码锁门	Single point password lock RV Door	08
房车窗系列/RV Window Series		
SW固定窗	SW Fixed window	09
SW推拉窗	SW Sliding window	10
SW双层推拉窗	SW Double Sliding window	11
HW双层外推窗 (圆角)	HW double extrapolation window (rounded corners)	12
HW双层外推窗 (方角)	HW double extrapolation window (Right Angle)	13
HW外推窗 (圆角单层钢化)	HW extrapolation window (rounded corner single Toughened glass)	14
推拉窗 (单侧内置纱窗)	Sliding window (one side built-in screen window)	15
提升窗	RV Lifting window	16
VENT排气扇	VENT exhaust fan	17
弧形外推窗	RV Arc extrapolation window	18
房车天窗	RV Skylight	19
房车天窗 (遥控灯光)	RV Skylight (remote control light)	20
前额天窗	RV Curved Skylight	21
星空窗	Starry sky window	22
踏步系列/RV Step Series		
MS-F手动 单层折叠踏步	MS-F manual folding Single step	23
MS-F手动 双层折叠踏步	MS-F manual folding Double step	24
MS-F电动 折叠踏步	MS-F Electric folding RV step	25
储物门、舱储门系列/Storage door、 warehousing door series		
HD储物门	HD Storage door	26
BD房车舱储门	BD Rv warehousing door	27

目录

Comtents

皮卡车窗系列/Pickup truck window series

皮卡前推拉窗	Pickup sliding window	28
皮卡后推拉窗	Pickup sliding window	29
皮卡大外推窗	Pickup extrapolation window	30
皮卡侧外推窗	Pickup extrapolation window	31

无框房车窗系列/Frameless RV window series

无框房车窗	Frameless RV window	32
-------	---------------------	----

配件系列/Accessories series

房车餐桌	RV Table	33
房车淋浴门	RV Shower Door	34
铝板 (车外身装饰铝板)	Aluminum plate (Aluminum body decoration)	35
导雨槽	Guide the rain trough	35
房车爬梯	RV ladder	36
铝封边条	aluminum Article sealing side	36

弧形房车门系列/Arc RV door series

弧形房车门	Arc RV door	37
-------	-------------	----



泰州市同发汽车配件有限公司

Taizhou Tongfa Automobile Fitting Co., Ltd

SLD Single point lock RV Door



High strength aluminum alloy profile powder coating



High strength aluminum mesh High strength glass fiber curtain



safety certified single point lock



Frosted tempered glass UV - resistant acrylic

Product Features and Main Functions

Door frame: high strength aluminum alloy profile, powder coating. Conventional color for black, white, can also be customized according to customer requirements silver gray, etc.

Door panel: white anti-ultraviolet ASA composite sandwich panel (other colors can be customized).

Glass: Frosted tempered glass or UV - resistant acrylic sheet is available.

Aluminum mesh: high strength aluminum mesh.

Gauze curtain: high strength glass fiber curtain.

Door lock: safety certified single point lock.

Structure: unique structure, the outer door and screen door can be combined together, but also separate.



Optional: see specification for details.

Optional parts: Door Stop. (Optional items must be ordered separately)
The door has opening, closing, locking, ventilation, light transmission, mosquito proof, sound insulation, heat insulation and good waterproof performance. Light structure, easy to install and use, firm and durable, various models.

Main uses

Trailer RV and self-propelled RV, suitable for wall thickness of 30~60mm.

Installation diagram



Door stop

Specification parameters

Specifications W-H	Dimensions/mm (W+19)-(H+19)	Opening size/mm (W)-(H)
622-1822	641-1841	622-1822
625-1750	644-1769	625-1750
625-1700	644-1719	625-1700
600-1600	619-1619	600-1600
600-1500	619-1519	600-1500
600-1350	619-1369	600-1350
650-1100	669-1119	650-1100
650-900	669-919	650-900
580-1750	599-1769	580-1750
530-1430	549-1449	530-1430

Specifications can be customized according to customer requirements.

W: Width of door mounting surface, unit mm;
H: Height of the door mounting surface, unit mm;

Specification

2R L Black
SLD-W-H- 4R - - White
4S R Silver gray (custom)

SLD: Specifications and models of doors

2R: A door with two rounded corners

4R : A door with four rounded corners

4S : A door with four right Angle

L: The hinges are on the left side of the door

R : The hinge is on the right side of the door

Black/White/Silver gray : Color of door frame

Accessories : Decorative rubber strip.

Optional parts : Door stop

(Optional items must be ordered separately)



泰州市同发汽车配件有限公司

Taizhou Tongfa Automobile Fitting Co., Ltd

ELD credit card lock RV Door



High strength aluminum alloy profile powder coating



High strength aluminum mesh
High strength glass fiber curtain



security certification electronic card lock



Frosted tempered glass
UV - resistant acrylic

Product Features and Main Functions

Door frame: High strength aluminum alloy profile, powder coating. Conventional color for black, white, can also be customized according to customer requirements silver gray, etc.

Door panel: White anti-ultraviolet ASA composite sandwich panel (other colors can be customized).

Glass: Frosted tempered glass or UV - resistant acrylic sheet is available.

Aluminum mesh: High strength aluminum mesh.

Gauze curtain: High strength glass fiber curtain.

Door lock: security certification electronic card lock, hotel type management.

Structure: unique structure, the outer door and screen door can be combined together, but also separate.

Optional: see specification for details.



Optional parts: Door STEP.(Optional items must be ordered separately)

The door has opening, closing, locking, ventilation, light transmission, mosquito proof, sound insulation, heat insulation and good waterproof performance. Light structure, easy to install and use, firm and durable, various models.

Main uses

Camp type trailer RV special, suitable for wall thickness of 30~60mm.

Installation diagram



Specification parameters

specifications W-H	Dimensions/mm (W+19)-(H+19)	Opening size/mm (W)-(H)
622-1822	641-1841	622-1822
625-1750	644-1769	625-1750
625-1700	644-1719	625-1700
600-1600	619-1619	600-1600
600-1500	619-1519	600-1500
600-1350	619-1369	600-1350
650-1100	669-1119	650-1100
650-900	669-919	650-900
580-1750	599-1769	580-1750
530-1430	549-1449	530-1430

Specifications can be customized according to customer requirements.

W: Width of door mounting surface, unit mm;

H: Height of the door mounting surface, unit mm;

Specification

2R L Black
ELD-W-H- 4R - White
4S R Silver gray (custom)

ELD: Specifications and models of doors

2R: A door with two rounded corners

4R: A door with four rounded corners

4S: A door with four right Angle

L: The hinges are on the left side of the door

R: The hinge is on the right side of the door

Black/White/Silver gray : color of door frame

Accessories : Decorative rubber strip.

Optional parts : Door STEP.

(Optional items must be ordered separately)



Door stop



High strength aluminum alloy profile powder coating



Automotive grade black privacy safety glass (3C certified).



Garbage can



Double point lock

Specification parameters


specifications W-H	Dimensions/mm (W+19)-(H+19)	Opening size/mm (W)-(H)
600-1810	626-1836	600-1810

Specifications can be customized according to customer requirements.

W: Width of door mounting surface, unit mm;

H: Height of the door mounting surface, unit mm;

Installation diagram



Product Features and Main Functions

Door frame: High strength aluminum alloy profile, powder coating. Conventional color for black, white, can also be customized according to customer requirements silver gray, etc.

Door panel: white anti-ultraviolet ASA composite sandwich panel (other colors can be customized).

Glass: Automotive grade black privacy safety glass (3C certified).

Screen door: Black pleated screen door.

Door lock: Imported double point lock.

Structure: The door with garbage can, handle, with open, close, lock, ventilation, light, mosquito proof, sound insulation, heat insulation and good waterproof performance. The structure is light, easy to install and use, firm and durable.

Optional: see specification for details.

Optional parts: Door STEP. (Optional items must be ordered separately)

Main uses

Trailer and self-propelled RV, suitable for wall thickness of 30-90mm

Specification

Black

DLD-W-H- 4R -R- White

Silver gray (custom)

DLD: Specifications and models of doors

4R : A door with four rounded corners

R : The hinge is on the right side of the door

Black/White/Silver gray : color of door frame

Accessories : Decorative rubber strip.

Optional parts : Door STEP.

(Optional items must be ordered separately)



Door stop





泰州市同发汽车配件有限公司

Taizhou Tongfa Automobile Fitting Co., Ltd

TLD Three point linkage lock RV Door



High strength aluminum alloy profile powder coating



High strength aluminum mesh
304 stainless steel diamond mesh
High strength glass fiber gauze



Three point linkage lock



UV - resistant acrylic

Product Features and Main Functions

Door frame: High strength aluminum alloy profile, powder coating. Conventional color for black, white, can also be customized according to customer requirements silver gray, etc.

Door panel: White uv resistant composite aluminum alloy (other colors can be customized).

Glass: Uv - resistant acrylic panel.

Aluminum mesh: High strength aluminum mesh or 304 stainless steel diamond mesh.

Gauze : High strength glass fiber gauze.

Air vent: Plastic labyrinth air vent is both ventilated and dustproof

Door lock: Unique three-point linkage lock.

Structure: Unique structure, the outer door and security door can be together, but also separate.

Optional: see specification for details.

Optional parts: Door suction.

(Optional items must be ordered separately)

The door has opening, closing, locking, ventilation, light transmission, mosquito proof, sound insulation, heat insulation and good waterproof performance. Light structure, easy to install and use, firm and durable, various models.

Main uses

Trailer and self-propelled RV. Suitable for wall thickness of 30mm - 40mm

Specification

2R L Black

TLD-W-H- 4R - - White

4S R Silver gray (custom)

TLD: Specifications and models of doors

2R: A door with two rounded corners

4R : A door with four rounded corners

4S : A door with four right Angle

L: The hinges are on the left side of the door

R : The hinge is on the right side of the door

Black/White/Silver gray : Color of door frame

Air vents should be specified

Accessories : Decorative rubber strip.

Optional parts : Door STEP.

(Optional items must be ordered separately)

Specification parameters



Specifications W-H	Dimensions/mm (W+19)-(H+19)	Opening size/mm (W)-(H)
625-1750	644-1769	625-1750
630-1630	649-1649	630-1630
630-1435	649-1454	630-1435

Specifications can be customized according to customer requirements.

W: Width of door mounting surface, unit mm;

H: Height of the door mounting surface, unit mm;

Installation diagram



Door STEP:





Teardrop RV Door



High strength aluminum alloy profile powder coating



High strength aluminum mesh
High strength glass fiber curtain



safety certified single point lock



Frosted tempered glass
UV - resistant acrylic



Product Features and Main Functions

Door frame: high strength aluminum alloy profile, powder coating. Conventional color for black, white, can also be customized according to customer requirements silver gray, etc.

Door panel: white anti-ultraviolet ASA composite sandwich panel (other colors can be customized).

Glass: Frosted tempered glass or UV - resistant acrylic sheet is available.

Aluminum mesh: high strength aluminum mesh.

Gauze curtain: high strength glass fiber curtain.

Door lock: safety certified single point lock.

Structure: unique structure, the outer door and screen door can be combined together, but also separate.


Optional: see specification for details.

Optional parts: Door Stop. (Optional items must be ordered separately)


Main uses

Trailer RV and self-propelled RV, suitable for wall thickness of 30-60mm.

Installation diagram



Opening size:



Specification parameters

Specifications W-H	Dimensions/mm (W+19)-(H+19)	Opening size/ mm (W)-(H)
622-1822	641-1841	622-1822
625-1750	644-1769	625-1750
625-1700	644-1719	625-1700
600-1600	619-1619	600-1600
600-1500	619-1519	600-1500
600-1350	619-1369	600-1350
650-1100	669-1119	650-1100
650-900	669-919	650-900
580-1750	599-1769	580-1750
530-1430	549-1449	530-1430

Specifications can be customized according to customer requirements.

W: Width of door mounting surface, unit mm;

H: Height of the door mounting surface, unit mm;

Specification

L Black

SLD-W-H- 4R - - White

R Silver gray (custom)

SLD: Specifications and models of doors

4R : A door with four rounded corners

L: The hinges are on the left side of the door

R : The hinge is on the right side of the door

Black/White/Silver gray : Color of door frame

Accessories : Decorative rubber strip.

Optional parts : Door stop

(Optional items must be ordered separately)

Door stop:





泰州市同发汽车配件有限公司

Taizhou Tongfa Automobile Fitting Co., Ltd

Trailer Door



High strength aluminum alloy profile powder coating



High strength aluminum mesh High strength glass fiber curtain



safety certified single point lock



Frosted tempered glass UV - resistant acrylic Toughened glass lifting window



Specification parameters

Specifications W-H	Dimensions/mm (W+19)-(H+19)	Opening size/mm (W)-(H)
650-900	669-919	650-900

Specifications can be customized according to customer requirements.

W: Width of door mounting surface, unit mm;
H: Height of the door mounting surface, unit mm;

Specification

- 2R L Black
- SLD-W-H- 4R - - White
- 4S R Silver gray (custom)

SLD: Specifications and models of doors

2R: A door with two rounded corners

4R : A door with four rounded corners

4S : A door with four right Angle

L: The hinges are on the left side of the door

R : The hinge is on the right side of the door

Black/White/Silver gray : Color of door frame

Accessories : Decorative rubber strip.

Optional parts : Door stop

(Optional items must be ordered separately)

Toughened glass lifting window : Door stop :



Product Features and Main Functions

Door frame: high strength aluminum alloy profile, powder coating. Conventional color for black, white, can also be customized according to customer requirements silver gray, etc.

Door panel: white anti-ultraviolet ASA composite sandwich panel (other colors can be customized).

Glass: Frosted tempered glass or UV - resistant acrylic sheet is available. (Toughened glass lifting window)

Aluminum mesh: high strength aluminum mesh.

Gauze curtain: high strength glass fiber curtain.

Door lock: safety certified single point lock.

Structure: unique structure, the outer door and screen door can be combined together, but also separate.


Optional: see specification for details.

Optional parts: Door Stop.(Optional items must be ordered separately)


Main uses

Trailer, suitable for wall thickness of 30~60mm.

Installation diagram



Opening size:





泰州市同发汽车配件有限公司

Taizhou Tongfa Automobile Fitting Co., Ltd

Single point credit card lock RV Door



High strength aluminum alloy profile powder coating



High strength aluminum mesh High strength glass fiber curtain



Frosted tempered glass UV - resistant acrylic



Single point credit card lock

Specification parameters

Specifications W-H	Dimensions/mm (W+19)-(H+19)	Opening size/mm (W)-(H)
622-1822	641-1841	622-1822
625-1750	644-1769	625-1750
625-1700	644-1719	625-1700
600-1600	619-1619	600-1600
600-1500	619-1519	600-1500
600-1350	619-1369	600-1350
650-1100	669-1119	650-1100
650-900	669-919	650-900
580-1750	599-1769	580-1750
530-1430	549-1449	530-1430

Specifications can be customized according to customer requirements.

W: Width of door mounting surface, unit mm;

H: Height of the door mounting surface, unit mm;

Specification

2R L Black

ELD-W-H- 4R - - White

4S R Silver gray (custom)

ELD: Specifications and models of doors

2R: A door with two rounded corners

4R : A door with four rounded corners


4S : A door with four right Angle

L: The hinges are on the left side of the door R : The hinge is on the right side of the door **Black/White/Silver gray** : color of door frame **Accessories** : Decorative rubber strip.

Optional parts : Door STEP.

(Optional items must be ordered separately)

Door STEP:



Product Features and Main Functions

Door frame: high strength aluminum alloy profile, powder coating. Conventional color for black, white, can also be customized according to customer requirements silver gray, etc.

Door panel: white anti-ultraviolet ASA composite sandwich panel (other colors can be customized).

Glass: Frosted tempered glass or UV - resistant acrylic sheet is available.

Aluminum mesh: high strength aluminum mesh.

Gauze curtain: high strength glass fiber curtain.

Door lock: safety certified Single point credit card lock.

Structure: unique structure, the outer door and screen door can be combined together, but also separate.

Optional: see specification for details.



Optional parts: Door Stop.

(Optional items must be ordered separately)

Main uses

Camp type trailer special, suitable for wall thickness of 30~60mm.

Installation diagram





泰州市同发汽车配件有限公司

Taizhou Tongfa Automobile Fitting Co., Ltd

Single point password lock RV Door



High strength aluminum alloy profile powder coating



High strength aluminum mesh High strength glass fiber curtain



Frosted tempered glass UV - resistant acrylic



Single point password lock

Product Features and Main Functions

Door frame: high strength aluminum alloy profile, powder coating. Conventional color for black, white, can also be customized according to customer requirements silver gray, etc.

Door panel: white anti-ultraviolet ASA composite sandwich panel (other colors can be customized).

Glass: Screen printed tempered glass.

Aluminum mesh: High strength aluminum mesh.

Gauze curtain: Folding shade.

Door lock: safety certified Single point password lock.

Structure: unique structure, the outer door and screen door can be combined together, but also separate.

Optional: see specification for details.



Optional parts: Door Stop.

(Optional items must be ordered separately)

Main uses

Camp type trailer special, suitable for wall thickness of 30~60mm.

Installation diagram



Specification parameters

Specifications W-H	Dimensions/mm (W+19)-(H+19)	Opening size/mm (W)-(H)
622-1822	641-1841	622-1822
625-1750	644-1769	625-1750
625-1700	644-1719	625-1700
600-1600	619-1619	600-1600
600-1500	619-1519	600-1500
600-1350	619-1369	600-1350
650-1100	669-1119	650-1100
650-900	669-919	650-900
580-1750	599-1769	580-1750
530-1430	549-1449	530-1430

Specifications can be customized according to customer requirements.

W: Width of door mounting surface, unit mm;

H: Height of the door mounting surface, unit mm;

Specification

2R L Black

ELD-W-H- 4R - - White

4S R Silver gray (custom)

ELD: Specifications and models of doors

2R: A door with two rounded corners

4R : A door with four rounded corners

4S : A door with four right Angle

L: The hinges are on the left side of the door R : The hinge is on the right side of the door **Black/White/Silver gray** : color of door frame **Accessories** : Decorative rubber strip.

Optional parts : Door STEP.

(Optional items must be ordered separately)

Door STEP:





SW Fixed window



Specification parameters

Specifications W-H	Dimensions/mm (W+30)-(H+30)	Opening size/mm (W)-(H)
500-300	530-330	500-300
500-350	530-380	500-350
500-400	530-430	500-400
500-450	530-480	500-450
500-500	530-530	500-500
550-400	580-430	550-400
600-500	630-530	600-500
700-400	730-430	700-400
700-450	730-480	700-450
700-500	730-530	700-500
700-550	730-580	700-550
750-400	780-430	750-400
750-430	780-460	750-430
800-450	830-480	800-450
800-500	830-530	800-500
800-600	830-630	800-600
800-700	830-730	800-700
800-800	830-830	800-800
900-450	930-480	900-450
900-500	930-530	900-500
1000-450	1030-480	1000-450
1000-500	1030-530	1000-500
1000-600	1030-630	1000-600
1100-450	1130-480	1100-450
1100-500	1130-530	1100-500
1200-300	1230-330	1200-300
1200-500	1230-530	1200-500
1300-550	1330-580	1300-550

Product Features and Main Functions

Window frame: High strength aluminum alloy profile, powder coating. The conventional colors are black and white, but also silver gray can be customized according to customer requirements.


Glass: 4mm toughened glass (certified for safety) or single layer UV resistant acrylic glass.

Gauze curtain: High strength glass fiber gauze curtain and shading curtain integration.(optional)

Open: Fixed window, not open.

Main function: The window has light transmission, mosquito proof, sound insulation, heat insulation and good waterproof performance. The window is fixed by tapping screw clamping wall, easy to install and use, lightweight structure, firm and durable, various models.

Installation diagram



Main uses

Used in Rv .
Suitable for different wall thickness: 30-90mm

Specifications can be customized according to customer requirements.

W: Width of door mounting surface, unit mm;

H: Height of the door mounting surface, unit mm;

Options: Integration of high-strength glass fiber gauze curtain and shading curtain.




Push up: Open the high-strength glass fiber gauze curtain.

Pull down: Open the shade



SW Sliding window



High strength
Aluminum alloy profile,
Powder coating



4mm toughened glass
(certified for safety)
Single layer
UV resistant acrylic glass



High strength glass fiber
Gauze curtain
Shading curtain integration

Specification parameters

Specifications W-H	Dimensions/mm (W+30)-(H+30)	Opening size/mm (W)-(H)
500-300	530-330	500-300
500-350	530-380	500-350
500-400	530-430	500-400
500-450	530-480	500-450
500-500	530-530	500-500
550-400	580-430	550-400
600-500	630-530	600-500
700-400	730-430	700-400
700-450	730-480	700-450
700-500	730-530	700-500
700-550	730-580	700-550
750-400	780-430	750-400
750-430	780-460	750-430
800-450	830-480	800-450
800-500	830-530	800-500
800-600	830-630	800-600
800-700	830-730	800-700
800-800	830-830	800-800
900-450	930-480	900-450
900-500	930-530	900-500
1000-450	1030-480	1000-450
1000-500	1030-530	1000-500
1000-600	1030-630	1000-600
1100-450	1130-480	1100-450
1100-500	1130-530	1100-500
1200-300	1230-330	1200-300
1200-500	1230-530	1200-500
1300-550	1330-580	1300-550

Specifications can be customized according to customer requirements.

W: Width of door mounting surface, unit mm;

H: Height of the door mounting surface, unit mm;

Product Features and Main Functions

Window frame: High strength aluminum alloy profile, powder coating. The conventional colors are black and white, but also silver gray can be customized according to customer requirements.


Glass: 4mm toughened glass (certified for safety) or single layer UV resistant acrylic glass.

Gauze curtain: High strength glass fiber gauze curtain and Shading curtain integration. (optional)

Open: push-pull type open, one side glass can push pull..

Main function: The window has light transmission, mosquito proof, sound insulation, heat insulation and good waterproof performance. The window is fixed by tapping screw clamping wall, easy to install and use, lightweight structure, firm and durable, various models.

Installation diagram



Main uses

Used in Rv . Suitable for different wall thickness: 30-90mm



SW Double Sliding window



High strength Aluminum alloy profile, Powder coating



Double layer UV resistant acrylic sheet



High strength glass fiber Gauze curtain Shading curtain integration

Specification parameters

Specifications W-H	Dimensions/mm (W+30)-(H+30)	Opening size/mm (W)-(H)
700-500	730-530	700-500
800-450	830-480	800-450
900-500	930-530	900-500

Specifications can be customized according to customer requirements.

W: Width of door mounting surface, unit mm;

H: Height of the door mounting surface,unit mm;

Main uses

Used in RV or buildings, suitable for different wall thickness: 30-80mm.

Product Features and Main Functions

Window frame: High strength aluminum alloy profile, powder coating.The conventional colors are black and white, but also silver gray can be customized according to customer requirements.


Glass: Double layer UV resistant acrylic sheet.

Gauze curtain: High strength glass fiber gauze curtain and Shading curtain integration.(optional)

Open: push-pull type open, one side glass can push pull..

Main function: The window has light transmission, mosquito proof, sound insulation, heat insulation and good waterproof performance.The window is fixed by tapping screw clamping wall, easy to install and use, lightweight structure, firm and durable, various models.

Installation diagram





HW double extrapolation window (Right Angle)



High strength Aluminum alloy profile, Powder coating



High strength glass fiber Gauze curtain Shading curtain integration



Double layer UV resistant acrylic sheet



Support bar

Specification parameters

Specifications W-H	Dimensions/mm (W+30)-(H+30)	Opening size/mm (W)-(H)
400-300	428-328	400-300
500-300	528-328	500-300
500-350	528-378	500-350
500-400	528-428	500-400
500-450	528-478	500-450
500-500	528-528	500-500
550-400	578-428	550-400
550-500	578-528	550-500
600-300	628-328	600-300
600-350	628-378	600-350
600-450	628-478	600-450
600-500	628-528	600-500
600-600	628-628	600-600
700-400	728-428	700-400
700-450	728-478	700-450
700-500	728-528	700-500
700-550	728-578	700-550
750-400	778-428	750-400
750-450	778-478	750-450
800-400	828-428	800-400
800-450	828-478	800-450
800-500	828-528	800-500
800-600	828-628	800-600
800-700	828-728	800-700
800-800	828-828	800-800
900-350	928-378	900-350
900-450	928-478	900-450
900-500	928-528	900-500
900-550	928-578	900-550
900-900	928-928	900-900
950-500	978-528	950-500
1000-450	1028-478	1000-450
1000-500	1028-528	1000-500
1000-600	1028-628	1000-600
1000-800	1028-828	1000-800
1100-450	1128-478	1100-450
1100-500	1128-528	1100-500
1100-550	1128-578	1100-550
1200-300	1228-328	1200-300
1200-350	1228-378	1200-350
1200-400	1228-428	1200-400
1200-500	1228-528	1200-500
1200-600	1228-628	1200-600
1220-705	1248-733	1220-705
1300-550	1328-578	1300-550
1450-500	1478-528	1450-500
1450-550	1478-578	1450-550

Product Features and Main Functions

Window frame: High strength aluminum alloy profiles, powder coating.

Window frame color: Normal color is black.

Glass: Double layer uv - resistant acrylic panel.

Gauze curtain: High strength fiberglass curtain and shading curtain.


Open: The window is equipped with a support rod, which can be pushed to open two angles, and can open up to 65 degrees.

Main functions: The window has the functions of opening, closing, ventilation, light transmission, shading, mosquito proof, sound insulation, heat insulation, privacy and good waterproof performance. When curtains and Windows are open, they can be used as emergency exits (except for small Windows). Light structure, easy to install and use, firm and durable, various models.

Main uses

Used in RV or buildings, suitable for different wall thickness: 30-80mm.

Installation diagram



Specifications can be customized according to customer requirements.

W: Width of door mounting surface, unit mm;

H: Height of the door mounting surface, unit mm



HW double extrapolation window (Right Angle)



High strength Aluminum alloy profile, Powder coating



High strength glass fiber Gauze curtain Shading curtain integration



Support bar



Double layer UV resistant acrylic sheet



Specification parameters

Specifications W-H	Dimensions/mm (W+50)-(H+50)	Opening size/mm (W) - (H)
350-280	400-330	350-280
400-300	450-350	400-300
500-300	550-350	500-300
500-350	550-400	500-350
500-400	550-450	500-400
500-450	550-500	500-450
500-500	550-550	500-500
550-400	600-450	550-400
550-500	600-550	550-500
600-300	650-350	600-300
600-350	650-400	600-350
600-450	650-500	600-450
600-500	650-550	600-500
600-600	650-650	600-600
700-400	750-450	700-400
700-450	750-500	700-450
700-500	750-550	700-500
700-550	750-600	700-550
750-400	800-450	750-400
750-450	800-500	750-450
800-400	850-450	800-400
800-450	850-500	800-450
800-500	850-550	800-500
800-600	850-650	800-600
800-700	850-750	800-700
800-800	850-850	800-800
900-350	950-400	900-350
900-450	950-500	900-450
900-500	950-550	900-500
900-550	950-600	900-550
900-900	950-950	900-900
950-500	1000-550	950-500
1000-450	1050-500	1000-450
1000-500	1050-550	1000-500
1000-600	1050-650	1000-600
1000-800	1050-850	1000-800
1100-450	1150-500	1100-450
1100-500	1150-550	1100-500
1100-550	1150-600	1100-550
1200-300	1250-350	1200-300
1200-350	1250-400	1200-350
1200-400	1250-450	1200-400
1200-500	1250-550	1200-500
1200-600	1250-650	1200-600
1220-705	1270-755	1220-705
1300-550	1350-600	1300-550
1450-500	1500-550	1450-500
1450-550	1500-600	1450-550

Product Features and Main Functions

Window frame: High strength aluminum alloy profiles, powder coating.

Window frame color: Normal color is black.

Glass: Double layer uv - resistant acrylic panel.

Gauze curtain: High strength fiberglass curtain and shading curtain.


Open: The window is equipped with a support rod, which can be pushed to open two angles, and can open up to 65 degrees.

Main functions: The window has the functions of opening, closing, ventilation, light transmission, shading, mosquito proof, sound insulation, heat insulation, privacy and good waterproof performance. When curtains and Windows are open, they can be used as emergency exits (except for small Windows). Light structure, easy to install and use, firm and durable, various models.

Main uses

Used in RV or buildings, suitable for different wall thickness: 30-80mm.

Installation diagram



Specifications can be customized according to customer requirements.

W: Width of door mounting surface, unit mm;

H: Height of the door mounting surface, unit mm;

HW extrapolation window (rounded corner single Toughened glass)



泰州市同发汽车配件有限公司

Taizhou Tongfa Automobile Fitting Co., Ltd



High strength
Aluminum alloy profile,
Powder coating



High strength glass fiber
Gauze curtain
Shading curtain integration



single Toughened glass)



Support bar

Specification parameters

Specifications W-H	Dimensions/mm (W+28)-(H+28)	Opening size/mm (W) - (H)
400-300	428-328	400-300
500-300	528-328	500-300
500-350	528-378	500-350
500-400	528-428	500-400
500-450	528-478	500-450
500-500	528-528	500-500
550-400	578-428	550-400
550-500	578-528	550-500
600-300	628-328	600-300
600-350	628-378	600-350
600-450	628-478	600-450
600-500	628-528	600-500
600-600	628-628	600-600
700-400	728-428	700-400
700-450	728-478	700-450
700-500	728-528	700-500
700-550	728-578	700-550
750-400	778-428	750-400
750-450	778-478	750-450
800-400	828-428	800-400
800-450	828-478	800-450
800-500	828-528	800-500
800-600	828-628	800-600
800-700	828-728	800-700
800-800	828-828	800-800
900-350	928-378	900-350
900-450	928-478	900-450
900-500	928-528	900-500
900-550	928-578	900-550
900-900	928-928	900-900
950-500	978-528	950-500
1000-450	1028-478	1000-450
1000-500	1028-528	1000-500
1000-600	1028-628	1000-600
1000-800	1028-828	1000-800
1100-450	1128-478	1100-450
1100-500	1128-528	1100-500
1100-550	1128-578	1100-550
1200-300	1228-328	1200-300
1200-350	1228-378	1200-350
1200-400	1228-428	1200-400
1200-500	1228-528	1200-500
1200-600	1228-628	1200-600
1220-705	1248-733	1220-705
1300-550	1328-578	1300-550
1450-500	1478-528	1450-500
1450-550	1478-578	1450-550

Product Features and Main Functions

Window frame: High strength aluminum alloy profiles, powder coating

Window frame color: Normal color is black.

Glass: 4mm toughened glass (certified for safety)

Gauze curtain: High strength fiberglass curtain and shading curtain.


Open: The window is equipped with a support rod, which can be pushed to open two angles, and can open up to 65 degrees.

Main function: The window has the functions of opening, closing, ventilation, light transmission, shading, mosquito proof, sound insulation, heat insulation, privacy and good waterproof performance. When curtains and Windows are open, they can be used as emergency exits (except for small Windows). Light structure, easy to install and use, firm and durable, various models

Main uses

Used in RV or buildings, suitable for different wall thickness: 30-80mm.

Installation diagram



Specifications can be customized according to customer requirements.

W: Width of door mounting surface, unit mm;

H: Height of the door mounting surface, unit mm;



Sliding window (one side built-in screen window)



High strength
Aluminum alloy profile,
Powder coating



One side built-in screen window



4mm single Toughened glass)



Product Features and Main Functions

Window frame: High strength aluminum alloy profile, powder coating. The conventional colors are black and white, but also silver gray can be customized according to customer requirements.


Glass: 4mm toughened glass (certified for safety).

Gauze curtain: One side built-in screen window

Open: Push-pull type open, one side glass can push pull.

Main function: The window has light transmission, mosquito proof, sound insulation, heat insulation and good waterproof performance. The window is fixed by tapping screw clamping wall, easy to install and use, lightweight structure, firm and durable, various models.

Installation diagram



Specification parameters

Specifications	Dimensions/mm	Opening size/mm
W-H	(W+30) - (H+30)	(W) - (H)
500-300	530-330	500-300
500-350	530-380	500-350
500-400	530-430	500-400
500-450	530-480	500-450
500-500	530-530	500-500
550-400	580-430	550-400
600-500	630-530	600-500
700-400	730-430	700-400
700-450	730-480	700-450
700-500	730-530	700-500
700-550	730-580	700-550
750-400	780-430	750-400
750-430	780-460	750-430
800-450	830-480	800-450
800-500	830-530	800-500
800-600	830-630	800-600
800-700	830-730	800-700
800-800	830-830	800-800
900-450	930-480	900-450
900-500	930-530	900-500
1000-450	1030-480	1000-450
1000-500	1030-530	1000-500
1000-600	1030-630	1000-600
1100-450	1130-480	1100-450
1100-500	1130-530	1100-500
1200-300	1230-330	1200-300
1200-500	1230-530	1200-500
1300-550	1330-580	1300-550

Specifications can be customized according to customer requirements.

W: Width of door mounting surface, unit mm;

H: Height of the door mounting surface, unit mm;

Main uses

Used in RV or buildings,
suitable for different wall thickness: 30-80mm.



RV Lifting window



High strength Aluminum alloy profile, Powder coating



High strength glass fiber Gauze curtain Shading curtain integration



4mm single Toughened glass



Product Features and Main Functions

Window frame: High strength aluminum alloy profile, powder coating. The conventional colors are black and white, but also silver gray can be customized according to customer requirements.


Glass: 4mm toughened glass (certified for safety).

Gauze curtain: High strength fiberglass curtain and shading curtain.

Open: Lift open, one side glass can lift.

Main function: The window has light transmission, mosquito proof, sound insulation, heat insulation and good waterproof performance. The window is fixed by tapping screw clamping wall, easy to install and use, lightweight structure, firm and durable, various models.

Installation diagram



Specification parameters

Specifications	Dimensions/mm	Opening size/mm
H-W	(H+30) - (W+30)	(H) - (W)
500-300	530-330	500-300
500-350	530-380	500-350
500-400	530-430	500-400
500-450	530-480	500-450
500-500	530-530	500-500
550-400	580-430	550-400
600-500	630-530	600-500
700-400	730-430	700-400
700-450	730-480	700-450
700-500	730-530	700-500
700-550	730-580	700-550
750-400	780-430	750-400
750-430	780-460	750-430
800-450	830-480	800-450
800-500	830-530	800-500
800-600	830-630	800-600
800-700	830-730	800-700
800-800	830-830	800-800
900-450	930-480	900-450
900-500	930-530	900-500
1000-450	1030-480	1000-450
1000-500	1030-530	1000-500
1000-600	1030-630	1000-600
1100-450	1130-480	1100-450
1100-500	1130-530	1100-500
1200-300	1230-330	1200-300
1200-500	1230-530	1200-500
1300-550	1330-580	1300-550

Specifications can be customized according to customer requirements.

W: Width of door mounting surface, unit mm;

H: Height of the door mounting surface, unit mm;

Main uses

Used in RV or buildings, suitable for different wall thickness: 30-80mm.



VENT exhaust fan



Privacy transparent lighting material




White anti-ULTRAVIOLET ASA material



Gauze



Installation diagram



Specification parameters

Specifications W-H	Dimensions/mm (W+78) - (H+78)	Opening size/mm (W) - (H)
280-280	358-358	280-280

Specifications can be customized according to customer requirements.

W: Width of door mounting surface, unit mm;

H: Height of the door mounting surface, unit mm;

Main uses

RV and self-propelled trailers.
Suitable for wall thickness of 25-65mm.

Product Features and Main Functions

Fan body: White anti-ULTRAVIOLET ASA material,
Top of the exhaust fan : Private transparent lighting material

Motor: The newly developed 12V and 20W DC motor is equipped with temperature control system to prevent overheating of the motor from affecting its service life.

Use: Simply press a button and ventilator can provide fresh air (air intake) and ventilation (air exhaust) to the car. Rain and snow weather can be closed in the case of the cover, still achieve ventilation function.

Main function: The exhaust fan has the characteristics of opening, closing, locking, ventilation, light transmission, mosquito proofing and good waterproof performance. Light structure, easy to install and use, firm and durable, various models.



RV Arc extrapolation window

Product pictures



Product features



Double layer UV resistant acrylic sheet



High strength Aluminum alloy profile, Powder coating



support rod

Specification parameters

Specifications W-H	Dimensions/mm (W+56)-(H+54)	Opening size/mm (W)-(H)
280-380	336-434	280-380
490-500	546-554	490-500
600-450	656-504	600-450
750-455	806-504	750-455
818-315	874-365	818-315
900-400	956-454	900-400
900-450	956-504	900-450
985-465	1041-519	985-465
960-450	1016-504	960-450

Specifications can be negotiated and customized according to user requirements.

W: Width of window mounting surface, unit: mm;

H: Arc length height of window mounting surface, unit: mm.

Main uses

RV
Suitable for wall thickness of 30-80mm.

Product Features and Main Functions

Window frame: High strength aluminum alloy profiles, powder coating.


Window frame color: Normal color is black.


Glass: Double layer uv - resistant acrylic panel.

Open: The window is equipped with a support rod, which can be pushed to open two angles, and can open up to 65 degrees.

Main functions: The window has the functions of opening, closing, ventilation, light transmission, shading, mosquito proof, sound insulation, heat insulation, privacy and good waterproof performance. When curtains and Windows are open, they can be used as emergency exits (except for small Windows). Light structure, easy to install and use, firm and durable, various models.

Installation diagram





High strength Aluminum alloy profile, Powder coating



High strength glass fiber Gauze curtain Shading curtain integration



Double layer UV resistant acrylic sheet



Gas support rod



Specification parameters

Specifications W-H	Dimensions/mm (W+127) - (H+127)	Opening size/mm (W) - (H)
450-400	577-527	450-400
500-500	627-627	500-500
700-500	827-627	700-500

Specifications can be customized according to customer requirements.




W: Width of door mounting surface, unit mm;

H: Height of the door mounting surface, unit mm;

Main uses

Used in RV or buildings, suitable for different wall thickness: 30-80mm.

Installation diagram



Product Features and Main Functions

Window frame: High strength aluminum alloy profiles, powder coating

Window frame color: Normal color is black.

Glass: Double layer uv - resistant acrylic panel.


Gauze curtain: High strength fiberglass curtain and shading curtain.

Open: The air brace can open up to 65°.

Main function: The window has the functions of opening, closing, ventilating, transmitting light, shading, mosquito proof, sound insulation, heat insulation, privacy and good waterproof performance. Light structure, easy to install and use, firm and durable.



RV Skylight (Remote control lights)



High strength Aluminum alloy profile, Powder coating



High strength glass fiber Gauze curtain Shading curtain integration



Double layer UV resistant acrylic sheet



Gas support rod

Product Features and Main Functions

Window frame: High strength aluminum alloy profiles, powder coating

Window frame color: Normal color is black.

Glass: Double layer uv - resistant acrylic panel.

Gauze curtain: High strength fiberglass curtain and shading curtain.

Open: The air brace can open up to 65°.

Light: A small light control key controls the opening and closing of the light

Main function: The window has the functions of opening, closing, ventilating, transmitting light, shading, mosquito proof, sound insulation, heat insulation, privacy and good waterproof performance. Light structure, easy to install and use, firm and durable.

Specification parameters

Specifications W-H	Dimensions/mm (W+127) - (H+127)	Opening size/mm (W) - (H)
450-400	577-527	450-400
500-500	627-627	500-500
700-500	827-627	700-500



Specifications can be customized according to customer requirements.

W: Width of door mounting surface, unit mm;
H: Height of the door mounting surface, unit mm;

Main uses

Used in RV or buildings, suitable for different wall thickness: 30-80mm.


Installation diagram





RV Curved Skylight

Product features



Double layer UV resistant acrylic sheet



Support rod



High strength Aluminum alloy profile, Powder coating



High strength glass fiber Gauze curtain Shading curtain integration

Product pictures



Product Features and Main Functions

Window frame: High strength aluminum alloy profiles, powder coating.

Window frame color: Normal color is black.

Glass: Double layer uv - resistant acrylic panel.

Gauze curtain: High strength fiberglass curtain and shading curtain.

Open: The window is equipped with a support rod, which can be pushed to open two angles, and can open up to 65 degrees.

Main functions: The window has the functions of opening, closing, ventilation, light transmission, shading, mosquito proof, sound insulation, heat insulation, privacy and good waterproof performance. When curtains and Windows are open, they can be used as emergency exits (except for small Windows). Light structure, easy to install and use, firm and durable, various models.

Main uses

Used in RV , suitable for different wall thickness: 30-80mm.

Specification parameters


Specifications W-H	Dimensions/mm (W+404)-(H+56)	Opening size/mm (W)-(H)
900-600	1304-656	900-600

Specifications can be negotiated and customized according to user requirements.

W: Width of window mounting surface, unit: mm;

H: Arc length height of window mounting surface, unit: mm.

Installation diagram





Starry sky window

Product pictures



Product features



Toughened glass



High strength
Aluminum alloy profile,
Powder coating

Application scenario



Specification parameters

Specifications W-H	Dimensions/mm (W+26)-(H+26)	Opening size/mm (W)-(H)
1200-1900	1226-1926	1200-1900

Specifications can be negotiated and customized according to user requirements.

W: Width of window mounting surface, unit: mm;
H: Arc length height of window mounting surface, unit: mm.

Product Features and Main Functions


Window frame: High strength aluminum alloy profile, powder coating. The conventional colors are black and white, but also silver gray can be customized according to customer requirements.

Glass: 4mm toughened glass (certified for safety)

Open: Fixed window, not open.

Main function: The window has light transmission, mosquito proof, sound insulation, heat insulation and good waterproof performance. The window is fixed by tapping screw clamping wall, easy to install and use, lightweight structure, firm and durable, various models.

Installation diagram



Main uses

Used in RV, suitable for different wall thickness: 30-80mm.



MS-F manual folding Single step

Product pictures



Product Features and Main Functions

Structural member: High strength carbon steel.

Pedals: High strength aluminum alloy profiles with anti-skid surface design.

Hardware: SUS304.

Appearance: Black coating on structural parts, anodized treatment on pedal surface, black can also be customized according to customer requirements.

Main function: Ingenious design, concealed installation, safe and reliable, easy to load 200KG. It can be installed on the chassis or load-bearing parts at the door of any vehicle for the convenience of getting on and off the vehicle.

Specification

MS-F-W- S

MS-F: Represents product code;

W: Represents the length of the net size of the step;

S: Represents the number of steps, single

Product features



High strength carbon steel



High strength aluminum alloy profiles with anti-skid surface design



SUS304



Specification parameters

Specifications W	Net size of pedal Length-Width	Spacing of mounting holes (W-20)
MS-F-450-S	450-210	430
MS-F-500-S	500-210	480
MS-F-550-S	550-210	530
MS-F-600-S	600-210	580

Specifications can be customized according to customer requirements.

W: The net size and length of the step pedal.

Installation diagram





MS-F manual folding Double step

Product pictures



Product Features and Main Functions

- Structural member:** High strength carbon steel.
- Pedals:** High strength aluminum alloy profiles with anti-skid surface design.
- Hardware:** SUS304.
- Appearance:** Black coating on structural parts, anodized treatment on pedal surface, black can also be customized according to customer requirements.
- Main function:** Ingenious design, concealed installation, safe and reliable, easy to load 200KG. It can be installed on the chassis or load-bearing parts at the door of any vehicle for the convenience of getting on and off the vehicle.

Specification

- MS-F-W- S**
- MS-F:** Represents product code;
- W:** Represents the length of the net size of the step;
- S:** Represents the number of steps, single

Product features



High strength carbon steel



High strength aluminum alloy profiles with anti-skid surface design



SUS304



Specification parameters

Specifications W	Net size of pedal Length-Width	Spacing of mounting holes (W-20)
MS-F-450-D	450-210	430
MS-F-500-D	500-210	480
MS-F-550-D	550-210	530
MS-F-600-D	600-210	580

Specifications can be customized according to customer requirements.

W: The net size and length of the step pedal.

Installation diagram





Product pictures



Double step



Single step

Product features



High strength carbon steel



SUS304



High strength aluminum alloy profiles with anti-skid surface design



Motor

Product Features and Main Functions

Structural member: High strength carbon steel.

Pedals: High strength aluminum alloy profiles with anti-skid surface design.

Hardware: SUS304.

Open: When the door is opened, the step will open automatically, and when the door is closed, the step will shrink automatically.

Appearance: Black coating on structural parts, anodized treatment on pedal surface, black can also be customized according to customer requirements.

Main function: Ingenious design, concealed installation, safe and reliable, easy to load 200KG. It can be installed on the chassis or load-bearing parts at the door of any vehicle for the convenience of getting on and off the vehicle.

Specification parameters



Specifications W	Net size of pedal length-width	Spacing of mounting holes (W-20)
E-F-450-S	450-210	430
E-F-500-S	500-210	480
E-F-550-S	550-210	530
E-F-600-S	600-210	580
E-F-450-D	450-210	430
E-F-500-D	500-210	480
E-F-550-D	550-210	530
E-F-600-D	600-210	580

Specifications can be customized according to customer requirements.



W: The net size and length of the step pedal.

Installation diagram

Single step:



Double step:



Specification

S
E-F-W- D

E-F: Represents product code;

W: Represents the length of the net size of the step;

S, D: Represents the number of steps, single, Double



HD Storage door

Product features



American made self tensioning tongue lock



Anti-ULTRAVIOLET ASA Aluminum alloy composite sandwich panel



High strength Aluminum alloy profiles



Aluminum alloy hinge

Product pictures



Application scenario



Product Features and Main Functions

Door frame: High strength aluminum alloy profiles.

Panel: Anti-ULTRAVIOLET ASA or Aluminum alloy composite sandwich panel.

Door lock: American self - tensioning tongue lock.

Hinge: Aluminum alloy hinge.

Appearance: Powder coating, white color as usual, black or silver gray as required.

Main functions: The storage door is easy to install, firm and durable, has low requirements on the accuracy of opening size, beautiful appearance, can be opened at 180°, and can be customized according to customer requirements.

Main uses

Camp type trailer special, suitable for wall thickness of 30~60mm.

Specification

T
B WH

HD-W-H- BL(custom)

L
R GR(custom)

HD: Represents product code;

W*H : Represents the width * height of the product mounting surface;

T/B/L/R: The position of hinge is above/below/left/right of the storage door;


WH/BL/GR : The colors are white/black/silver gray.

Specification parameters

Specifications W-H	Dimensions/mm (W+26)-(H+26)	Opening size/mm (W)-(H)
400-300	426-326	400-300
450-350	476-376	450-350
500-300	526-326	500-300
500-350	526-376	500-350
500-400	526-426	500-400
600-300	626-326	600-300
600-450	626-476	600-450
650-350	676-376	650-350
650-480	676-506	650-480
700-200	726-226	700-200
700-300	726-326	700-300
700-500	726-526	700-500
700-600	726-626	700-600
800-500	826-526	800-500
800-600	826-626	800-600
900-300	926-326	900-300
900-500	926-526	900-500
1100-500	1126-526	1100-500

Specifications can be customized according to customer requirements.

Installation diagram





BD Rv warehousing door

Product features



High strength aluminum alloy profile powder spraying



Powder coated High-strength aluminum alloy




mechanical linkage Three point lock



Air spring support rod For automobiles

Installation diagram



Product Features and Main Functions

Door frame: High strength aluminum alloy profile, powder spraying. The regular colors are black and white, or silver gray can be customized according to customer requirements.

Panel: Powder coated high-strength aluminum alloy panel/non-slip aluminum plate, painted in black, white, silver gray or aluminum alloy color, can also be customized according to customer requirements.

Support rod: Air spring support rod for automobiles.

Open: lift open with an opening Angle greater than 90°

Door lock: mechanical linkage three point lock.

Main functions: The door of The storeroom realizes The function of opening, closing and locking. Light structure, easy to install and use, firm and durable, various models.

Options:

1. The panel is Sprayed aluminum sheet;
2. Non-slip aluminum panel.

Main uses

Used in the storage room of RV.

Specification parameters

Specifications W-H	Dimensions/mm (W+50)-(H+56)	Opening size/mm (W)-(H)
1524-450	1574-506	1524-450
1524-380	1574-436	1524-380
1524-385	1574-441	1524-385

Specifications can be customized according to customer requirements.

W: Width of door mounting surface, unit mm;
H: Height of the door mounting surface, unit mm;

Application scenario




Product pictures





Pickup sliding window

Product pictures



Product features

Product Features and Main Functions

Window frame: High strength aluminum alloy profile, powder spraying.
The conventional colors are black and white, Silver gray can also be customized according to customer requirements.

Glass: 3mm tempered glass (with safety certification).

Opening: Push-pull opening,
The middle glass can be pushed and pulled.

Main functions:The window has good functions of light transmission, sound insulation and mosquito prevention. The sliding window adopts self tapping screws to fix the wall, which has the advantages of simple installation and use, light structure, firmness and durability, and various models.



High strength aluminum alloy
Powder spraying



Push-pull opening



3mm tempered glass


Main uses

This product is applicable to all types of pickup trucks

Specification parameters

Specifications can be negotiated and customized according to user requirements.

Installation diagram





Pickup sliding window

Product features



3mm tempered glass



Push-pull opening



One sided screen window



High strength aluminum alloy Powder spraying

Product pictures



Product Features and Main Functions

Window frame: High strength aluminum alloy profile, powder spraying. The conventional colors are black and white, Silver gray can also be customized according to customer requirements.

Glass: 3mm tempered glass (with safety certification).

Opening: push-pull type open, one side glass can push pull.

Window screen: One side built-in removable screen window

Main functions:The window has good functions of light transmission, sound insulation and mosquito prevention. The sliding window adopts self tapping screws to fix the wall, which has the advantages of simple installation and use, light structure, firmness and durability, and various models.

Specification parameters


Specifications can be negotiated and customized according to user requirements.

Main uses

This product is applicable to all types of pickup trucks

Installation diagram

Opening size





Pickup extrapolation window

Product pictures



Product Features and Main Functions

Window frame: High strength aluminum alloy profile, powder spraying.

Window frame color: Normal color is black.

Glass: 3mm tempered glass (with safety certification).

Opening: The window is equipped with a gas support rod, which can be pushed out.

Main functions: The window has the functions of opening, closing, ventilation, light transmission, sun shading Anti mosquito, sound insulation, heat insulation, privacy and other functions and Good waterproof performance. Available when screens and windows are open As an emergency exit (except for small windows). Lightweight structure, It is easy to install and use, firm and durable, and has various models.

Product features



3mm tempered glass (with safety certification)



High strength aluminum alloy Powder spraying



Air support rod

Specification parameters


Specifications can be negotiated and customized according to user requirements.

Main uses

This product is applicable to all types of pickup trucks

Installation diagram


Opening size





Pickup extrapolation window

Product features



High strength aluminum alloy
Powder spraying



3mm tempered glass
(with safety certification)



Self tensioning tongue lock



Air support rod

Product pictures



Product Features and Main Functions

Window frame: High strength aluminum alloy profile, powder spraying.

Window frame color: Normal color is black.

Glass: 3mm tempered glass (with safety certification).

Window lock: Self tensioning tongue lock

Opening: The window is equipped with a gas support rod, which can be pushed out.

Main functions: The window has the functions of opening, closing, ventilation, light transmission, sun shading Anti mosquito, sound insulation, heat insulation, privacy and other functions and Good waterproof performance. Available when screens and windows are open As an emergency exit (except for small windows). Lightweight structure, It is easy to install and use, firm and durable, and has various models.

Specification parameters


Specifications can be negotiated and customized according to user requirements.

Main uses

This product is applicable to all types of pickup trucks

Installation diagram

Opening size





Frameless RV window

Product features



Double layer uv - resistant acrylic panel



High strength aluminum alloy hinges



Air support rod



High strength glass fiber Gauze curtain Shading curtain integration

Product pictures



Product Features and Main Functions

Window hinges: High strength aluminum alloy profiles, powder coating.

Window hinges color: Normal color is black.

Glass: Double layer uv - resistant acrylic panel.

Gauze curtain: High strength fiberglass curtain and shading curtain.

Open: The window is equipped with a support rod, which can be pushed to open two angles, and can open up to 65 degrees.

Main functions: The window has the functions of opening, closing, ventilation, light transmission, shading, mosquito proof, sound insulation, heat insulation, privacy and good waterproof performance. When curtains and Windows are open, they can be used as emergency exits (except for small Windows). Light structure, easy to install and use, firm and durable, various models.

Specification parameters

Specifications W-H	Dimensions/mm (W+90)-(H+90)	Opening size/mm (W)-(H)
700-500	790-590	700-500

Specifications can be customized according to customer requirements.


W: Width of window mounting surface, unit mm;

H: Height of the window mounting surface, unit mm;

Main uses

For RV; suitable for different wall thickness: 30-80mm.

Installation diagram





Product features



High strength aluminum alloy panel



High strength aluminum alloy frame



Rotary tongue lock




Aluminium alloy hinge

Specification parameters

Specifications W-H	Dimensions/mm (W)-(H)	Opening size/mm (W)-(H)
800-450	800-450	800-450

Specifications can be customized according to customer requirements.

Installation diagram



Product pictures



Product Features and Main Functions

Table borders: High strength aluminum alloy profile.

Table panel : High strength aluminum alloy plate.

Lock: Rotary tongue lock.

Hinge: Aluminum alloy hinge.

Main function: The small table is easy to install, firm and durable, installed on the outside of the car body, easy to install, beautiful and generous

Main uses

Trailer and self-propelled RV.

Description


Size: 800mm X 450mm X 20mm

Product Weight: 5KG


Weight carried: 30KG



Product features



Honeycomb structure
Non-woven fabric



High strength
Aluminum alloy frame

Product pictures



Product Features and Main Functions

Frame: High strength aluminum alloy profile.

Shower Curtain: Honeycomb non-woven fabric.

Appearance: The conventional colors are sky blue and beige; it can also be customized according to customer requirements.

Main functions: This product adopts honeycomb like structure, waterproof and mildew proof non-woven cloth surface Material, heat insulation, noise reduction, heat preservation and cooling. Push-pull opening maximum Save shower space, after unfolding, dry and wet separation, no dead corner, rest assured to shower. After folding, it does not occupy space and is beautiful


Specification parameters

Specifications can be customized according to customer requirements.

Main uses

RV and buildings.

Product structure





Aluminum plate (Aluminum body decoration) & Guide the rain trough

泰州市同发汽车配件有限公司

Taizhou Tongfa Automobile Fitting Co., Ltd

Aluminum plate (Aluminum body decoration)

Product pictures



Application scenarios



Specification parameters

Specifications can be customized according to customer requirements.

Product Features and Main Functions

Aluminum plate: High strength aluminum alloy surface anti ultraviolet roller coating.

Color of aluminum plate: The conventional color is white.

Installation: The aluminum plate is fixed on the body frame by inserting.


Main functions: This piece is used as the exterior decoration of the RV. It is easy to install and can effectively reduce the body weight. It is high-end, beautiful and atmospheric.

Guide the rain trough

Product pictures



Description



Specification parameters

Specifications can be customized according to customer requirements.

Product Features and Main Functions

Rain chute: High strength aluminum alloy profile, powder spraying.

Color: The general color is white.

Installation: Install the rain chute above the door of the RV.

Main functions: The upper edge of the RV door guides the rainwater to improve the sealing stability of the RV door. The rain guide groove is easy to install.



RV ladder&aluminum Article sealing side

RV ladder

Product pictures



Specification parameters

Specifications can be negotiated and customized according to user requirements.

W: The width of the RV ladder, unit mm;

H: The height of the RV ladder, unit mm.

Product Features and Main Functions

RV Ladder: High strength aluminum alloy profiles, powder spraying.


RV Ladder color: The normal color is white and black.

Mounting: Screw mounted in proper position.

Main functions: It is convenient for people to get on and off the rv roof. The load bearing can reach 200KG. It is durable and will not be deformed for a long time. The ladder structure is light and easy to install and use.

aluminum Article sealing side

Product pictures



Specification parameters

Specifications can be negotiated and customized according to customer requirements.

The length, Angle, etc of the Article sealing side

Product Features and Main Functions

Aluminum Article sealing side: High strength aluminum alloy profiles, powder coating.

Color of aluminum strip: White and black are the normal colors.

Installation: Install Article sealing side at the joint of the top and side of the RV.

Main functions: This piece is used as the top and side splicing part of the rv to draw the edge, and has the sealing and aesthetic function, easy to install.




Product pictures



Product features



UV - resistant acrylic



High strength aluminum alloy



safety certified single point lock

Product Features and Main Functions

Door frame: High strength aluminum alloy profile, The color can be customized according to customer requirements.

Door panel: White UV resistant ASA composite sandwich panel (other colors can be customized).

Glass: UV resistant acrylic plate.

Door lock: safety certified single point lock.

Structure: Unique structure. The door has opening, closing, locking, ventilation, light transmission, sound insulation, heat insulation and good waterproof performance. Light structure, easy installation and use, firm and durable, and various models

Specification parameters

Specifications can be customized according to user requirements.

Main uses

RV

Installation diagram



企业质量方针 Enterprise quality policy

客户至上，奋斗为本
Customer first, strive for the base
质量为本，齐心协力
Quality - oriented, win-win cooperation.

企业愿景 Enterprise vision

匠心成就您的美好生活
Focus on achieving your better life

企业使命 Corporate mission

至诚至信，合作共赢
Sincerity to letter, win-win cooperation

企业核心价值观 Company Core Values

务实奋进，以人为本
Pragmatic forge ahead, people-oriented
开拓创新，客户为先
pioneering and innovative, customer first.